

STROCO P/N	SHELL SIZE	T THR'D UNC-3B	"A" (+/- .003)	"B" (+.015/- .015)	"C" (+.015/- .000)	"D"	"E" (+.020/- .020)	"F" (+.015/- .000)
S900T-8	8	.112-40	0.594	0.880	0.516	.106/.166	0.308	0.286
S900T-10	10	.112-40	0.719	1.005	0.641	.106/.166	0.433	0.286
S900T-12	12	.112-40	0.812	1.098	0.766	.106/.166	0.526	0.286
S900T-14	14	.112-40	0.906	1.192	0.891	.106/.166	0.620	0.286
S900T-16	16	.112-40	0.969	1.255	1.016	.106/.166	0.683	0.286
S900T-18	18	.112-40	1.062	1.348	1.141	.106/.166	0.776	0.286
S900T-20	20	.112-40	1.156	1.500	1.266	.106/.166	0.812	0.343
S900T-22	22	.112-40	1.250	1.593	1.391	.106/.166	0.907	0.343
S900T-24	24	.138-32	1.375	1.750	1.516	.123/.183	1.000	0.375
S900T-28	28	.138-32	1.562	2.000	1.766	.123/.183	1.125	0.438
S900T-32	32	.138-32	1.750	2.312	2.062	.123/.183	1.188	0.562
S900T-36	36	.138-32	1.938	2.500	2.312	.123/.183	1.375	0.562

SPECIFICATIONS


MATERIAL: Retainer- Aluminum alloy, 6061-T6 per QQ-A-250/11, .032" (+.003/ -.003) thickness
 Nut- Self-Locking, clinch type, corrosion resistant alloy steel per AMS5640 (type 303)
 Performance per MIL-N-25027

FINISH: Retainer- Alodine per MIL-C-5541 CI 1A
 Optional- Epoxy Polyamide primer applied per MIL-P-23377
 Nut- Per MIL-N-45938 with dry film lubricant applied per MIL-L-46010

NOTES: The A, B, C, and E dimensions are to be measured in the restrained position.
 This data sheet represents all options for this series, see ordering info page for part specifics.
 Parts to be marked with the respective S900T-XXX part number, if there is enough space.

DIMENSIONS IN INCHES: TOLERANCES UNLESS OTHERWISE SPECIFIED: X.XX +/- .030"; X.XXX +/- .010"; ANGLES +/- .05*

DOCUMENT AND ITS CONTENTS ARE PROPRIETARY INFORMATION TO STROCO AND ITS AFFILIATES, USE WITHOUT AUTHORIZATION IS PROHIBITED.

<u>CAGE NO.</u> 19904	<u>TITLE</u> NUT PLATE		<u>PART NUMBER</u> S900T
DRAWING FOR INTERNAL USE ONLY			REV B 12/30/07