



STROCO P/N	SHELL SIZE	T THR'D UNC-3B	"A" (+/- .003)	"B" (+.015/- .015)	"C" (+.015/- .000)	"D"
S921-8	8	.112-40	0.594	0.880	0.570	.106/.166
S921-10	10	.112-40	0.719	1.005	0.700	.106/.166
S921-12	12	.112-40	0.812	1.098	0.820	.106/.166
S921-14	14	.112-40	0.906	1.192	0.945	.106/.166
S921-16	16	.112-40	0.969	1.255	1.070	.106/.166
S921-18	18	.112-40	1.062	1.348	1.196	.106/.166
S921-20	20	.112-40	1.156	1.500	1.320	.106/.166
S921-22	22	.112-40	1.250	1.625	1.440	.106/.166
S921-24	24	.138-32	1.375	1.750	1.570	.123/.183
S921-25	25	.138-32	1.500	1.891	1.658	.123/.183

SPECIFICATIONS

MATERIAL: Retainer- Aluminum alloy, 6061-T6 per QQ-A-250/11, .037" (+.005/ -.005) thickness
Nut- Self-Locking, clinch type, corrosion resistant alloy steel per AMS5640 (type 303)
Performance per MIL-N-25027

FINISH: Retainer- Alodine per MIL-C-5541 CI 1A
Optional- Epoxy Polyamide primer applied per MIL-P-23377
Nut- Per MIL-N-45938 with dry film lubricant applied per MIL-L-46010

NOTES: See ordering information for additional options.
Parts to be marked with the respective S921-XX part number, if there is enough space.

DIMENSIONS IN INCHES: TOLERANCES UNLESS OTHERWISE SPECIFIED: X.XX +/- .030"; X.XXX +/- .010"; ANGLES +/- .05*

DOCUMENT AND ITS CONTENTS ARE PROPRIETARY INFORMATION TO STROCO AND ITS AFFILIATES. USE WITHOUT AUTHORIZATION IS PROHIBITED.

<u>CAGE NO.</u> 19904	<u>TITLE</u> NUT PLATE DRAWING FOR INTERNAL USE ONLY		<u>PART NUMBER</u> S921-XX REV B 12/30/07
--------------------------	---	--	--