

STROCO P/N	SHELL SIZE	T THR'D UNC-3B	"A" (+/- .003)	"B" (+.015/- .015)	"C" (+.015/- .000)	"D"	"E" (+.020/- .020)
S924-8C	8	.138-32	0.734	1.093	0.697	.123/.183	0.375
S924-10C	10	.138-32	0.812	1.171	0.789	.123/.183	0.453
S924-12C	12	.138-32	0.938	1.296	0.967	.123/.183	0.579
S924-14C	14	.138-32	1.031	1.390	1.099	.123/.183	0.672
S924-16C	16	.138-32	1.125	1.484	1.231	.123/.183	0.766
S924-18C	18	.138-32	1.203	1.562	1.342	.123/.183	0.844
S924-20C	20	.138-32	1.297	1.656	1.437	.123/.183	0.938
S924-22C	22	.138-32	1.375	1.734	1.531	.123/.183	1.016
S924-24C	24	.138-32	1.500	1.859	1.656	.123/.183	1.141

### SPECIFICATIONS


**MATERIAL:** Retainer- Aluminum alloy, 2024-T3 per QQ-A-250/4, .040" (+.003/ -.003) thickness  
 Nut- Self-Locking, clinch type, corrosion resistant alloy steel per AMS5640 (type 303)  
 Performance per MIL-N-25027

**FINISH:** Retainer- Alodine per MIL-C-5541 CI 1A  
 Optional- Epoxy Polyamide primer applied per MIL-P-23377  
 Nut- Per MIL-N-45938 with dry film lubricant applied per MIL-L-46010

**NOTES:** The A, B, C, and E dimensions are to be measured in the restrained position.  
 Parts to be marked with the respective S924-XXC part number, if there is enough space.

DIMENSIONS IN INCHES: TOLERANCES UNLESS OTHERWISE SPECIFIED: X.XX +/- .030"; X.XXX +/- .010"; ANGLES +/- .05\*

DOCUMENT AND ITS CONTENTS ARE PROPRIETARY INFORMATION TO STROCO AND ITS AFFILIATES, USE WITHOUT AUTHORIZATION IS PROHIBITED.

<u>CAGE NO.</u> 19904	<u>TITLE</u> <b>NUT PLATE</b>		<u>PART NUMBER</u> <b>S924-XXC</b>
	DRAWING FOR INTERNAL USE ONLY		REV B 12/30/07