



STROCO P/N	SHELL SIZE	T THR'D UNC-3B	"A" (+/- .003)	"B" (+.015/- .015)	"C"/2 (+.015/- .000)	"D"	"F" (+.015/- .000)
S933-3CX	3	.112-40	0.625	0.925	0.320	.106/.166	0.300
S933-6CX	6	.112-40	0.469	0.766	0.183	.106/.166	0.298
S933-7CX	7	.112-40	0.719	1.016	0.359	.106/.166	0.298
S933-8CX	8	.112-40	0.594	0.891	0.277	.106/.166	0.296
S933-10CX	10	.112-40	0.719	1.016	0.359	.106/.166	0.298
S933-12CX	12	.112-40	0.812	1.109	0.425	.106/.166	0.296
S933-14CX	14	.112-40	0.906	1.203	0.492	.106/.166	0.296
S933-16CX	16	.112-40	0.969	1.266	0.547	.106/.166	0.298
S933-18CX	18	.112-40	1.062	1.390	0.610	.106/.166	0.328
S933-19CX	19	.112-40	0.906	1.203	0.492	.106/.166	0.296
S933-20CX	20	.112-40	1.156	1.510	0.672	.106/.166	0.354
S933-22CX	22	.112-40	1.250	1.640	0.739	.106/.166	0.390
S933-24CX	24	.138-32	1.375	1.760	0.797	.123/.183	0.386
S933-25CX	25	.138-32	1.500	1.859	0.845	.123/.183	0.358
S933-27CX	27	.112-40	0.969	1.266	0.547	.106/.166	0.298
S933-28CX	28	.138-32	1.562	2.000	0.920	.123/.183	0.438
S933-32CX	32	.138-32	1.750	2.312	1.058	.123/.183	0.562
S933-36CX	36	.138-32	1.938	2.500	1.170	.123/.183	0.562
S933-37CX	37	.112-40	1.187	1.500	0.670	.106/.166	0.314
S933-61CX	61	.112-40	1.437	1.812	0.812	.106/.166	0.376

SPECIFICATIONS

MATERIAL: Retainer- Aluminum alloy, 6061-T6 per QQ-A-250/11, .037" (+.005/ -.005) thickness
Nut- Self-Locking, clinch type, corrosion resistant alloy steel per AMS5640 (type 303)
Performance per MIL-N-25027

FINISH: Retainer- Alodine per MIL-C-5541 CI 1A
Optional- Epoxy Polyamide primer applied per MIL-P-23377
Nut- Per MIL-N-45938 with dry film lubricant applied per MIL-L-46010

NOTES: See ordering information for additional options.
Parts to be marked with the respective S933-XXCX part number, if there is enough space.

DIMENSIONS IN INCHES: TOLERANCES UNLESS OTHERWISE SPECIFIED: X.XX +/- .030"; X.XXX +/- .010"; ANGLES +/- .05*

DOCUMENT AND ITS CONTENTS ARE PROPRIETARY INFORMATION TO STROCO AND ITS AFFILIATES. USE WITHOUT AUTHORIZATION IS PROHIBITED.

CAGE NO. 19904	TITLE NUT PLATE	PART NUMBER S933-XXCX
DRAWING FOR INTERNAL USE ONLY		REV B 12/30/07

